



AMMONIA DIGITAL SENSOR PRODUCT SPECIFICATION SHEET

IOT application Features Supportive

Real Time Continuous Measurement

Built-In Temperature Compensation

The OXYSERIES (NH4D-103+ Series sensors) feature 3 Wire Adjustable Digital output high accurate upgrade measurement technology, Designed for most water applications,

Typical applications include:

- Industrial wastewater
- Aquaculture & Tap water
- Agriculture
- RO & Beverages & Food Stuffs
- Environmental monitoring

The NH4D103 + Sensor gives you the options of output RS485, maximize sensor life. Sensors can be used in new installations with flow cell or immersion type, installed as a replacement for other 4-20mA output free AMMONIA sensors (Consult with OXY SERIES for compatibility).

SPECIFICATIONS

Measuring Range	0.1 to 1000 ppm or mg/l
Classification	IP68/NEMA6P
Housing material	PP Main body PVC Cable
Temp Range	0-50 °C.
Accuracy	± 2.5%
Temp compensation	NTC10K
Output	MODBUS RS485
Cable Length	10M
Calibration	Standard Solution , Comparison Calibration
Pressure Range	≤0.3Mpa
Size	Diameter 30mm* Length 160mm
Power supply	DC 12V-24V DC